# Nipol® LX852B

### Latex

### **Zeon Corporation**

### Message:

Acrylate latex

Characteristics

Soft type. Excellent adhesiveness, resistant to discoloration from light and age. Extremely low formaldehyde. LX852B is included in the Japan Sanitary Material Industrial Association's list.

Applications

Rough blankets, clothing materials (impregnated), wet tissues, sanitation materials and filters.

Filters(internal) and clutch sheets.

Glass fibers (internal).

General Information			
Features	Copolymer		
	Crosslinkable		
	Good Adhesion		
	Soft		
Uses	Filters		
	Sanitary Products		
Physical	Nominal Value	Unit	
Solution Viscosity	80	mPa∙s	
рН	6.5		
Surface Tension	30	mN/m	
Total Solids	45	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Unit

°C

Test Method

DSC

Nominal Value

-6.00

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Thermal

Glass Transition Temperature

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

