

Shin-Etsu Elastomer SFX-14032AU

Fluorosilicone

Shin-Etsu Silicones of America

Message:

Shincor SFX-14032AU is normal 90 durometer fluorosilicone compounds. It is designed to process well in molding applications.
Excellent fuel and solvent resistance.
Usable over a broad temperature range.

General Information		
Features	Solvent resistance	
	Workability, good	
	Fuel resistance	
Physical	Nominal Value	Unit
Specific Gravity	1.47	g/cm³
Hardness	Nominal Value	Unit
Durometer Hardness	87	
Elastomers	Nominal Value	Unit
Tensile Stress (100% Strain)	4.27	MPa
Tensile Strength	7.28	MPa
Additional Information	Nominal Value	
Cure Agent	DBPH	

Press / Post Cure: Post

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

