

Sylvin 8230-84LGUV Natural

Polyvinyl Chloride
Sylvin Technologies Incorporated

Message:
Sylvin 8230-84LGUV Natural Is A Vinyl Compound Formulated For General Purpose Extrusion Or Molding Applications That Require A Matt Finish And A UV Stabilizer.

General Information			
Additive	UV Stabilizer		
Features	General Purpose		
	Good UV Resistance		
Uses	General Purpose		
Appearance	Matte Finish		
	Natural Color		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.35	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	84		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	15.9	MPa	ASTM D638
Tensile Elongation (Break)	330	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	74.4	kN/m	ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT