MAZMID 6.10

Polyamide 610

Mazzaferro Indústria e Comércio de Polímeros e Fibras Ltda.

Message:

MAZMID 6.10 is a Polyamide 610 (Nylon 610) product. It is available in Latin America. Characteristics include: Good Dimensional Stability Low Moisture Absorption Medium Viscosity

General Information	
Features	Good Dimensional Stability
	Low Moisture Absorption
	Medium Viscosity

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.07 to 1.09	g/cm³	
Melt Mass-Flow Rate (MFR) (235°C/2.16			
kg)	12 to 20	g/10 min	
Water Absorption (23°C, 24 hr)	0.30 to 0.45	%	
Viscosity Number	140 to 165	cm³/g	ISO 307
Relative Viscosity - H2SO4	2.60 to 2.90		
Monomers	< 1.3	%	
Thermal	Nominal Value	Unit	
Melting Temperature	212 to 216	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

