

# ExxonMobil™ PP2252E4

Polypropylene Homopolymer

ExxonMobil Chemical

## Message:

A homopolymer resin with moderate melt flow rate for fabrics requiring high-speed extrusion and low water carrying capacity.

General Information			
Features	Equilibrium rigidity/toughness		
	Low water portability		
	General		
Uses	Packaging		
	Carpet backing		
	Composite		
	Fiber		
	Fabric		
Appearance	Natural color		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	4.2	g/10 min	ASTM D1238
Legal statement			

未经埃克森美孚化工书面允许,这种产品包括其产品名称,不得在任何医疗应用领域予以使用或有关潜在食品接触应用合规信息(例如:FDA,EU,HPFB),请与埃克森美孚化工客户服务代表联系。

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT