

PETILEN I15-19T

Low Density Polyethylene

PETKIM Petrokimya Holding A.S.

Message:

PETILEN I15-19T is a low density polyethylene product. It can be processed by injection molding and is available in North America, Europe or the Asia-Pacific region. PETILEN I15-19T applications include hats/caps/corks, kitchen utensils, consumer goods and additives/masterbatches.

General Information			
Uses	Kitchen utensils		
	Shield		
	Masterbatch		
	Shell		
	Toys		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	0.917 - 0.921	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	13 - 17	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

