

Artenius WHITE+

Polyethylene Terephthalate

Artenius

Message:

Artenius WHITE+ is a copolymer of PET (Polyethylene-Terephthalate), delivered in resin pellets. It is suitable for the stretch blow moulding process in one or two stages. This resin has been specially conceived for dairy products. This resin has suitable protection against the visible and UV light which preserves the nutritional properties extending shelf life.

Thanks to its formulation, it has excellent organoleptic properties in the conversion process which this kind of package demands.

General Information			
Features	Copolymer		
	Food Contact Acceptable		
	Good Organoleptic Properties		
	Good UV Resistance		
Uses	Bottles		
	Food Packaging		
Agency Ratings	EU 94/62/EC		
	EU No 10/2011		
Forms	Pellets		
Processing Method	Stretch Blow Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.47	g/cm ³	
Apparent Density	0.89	g/cm ³	
Viscosity Number (Reduced Viscosity)	78.0 to 82.0	ml/g	ISO 1628
Acetaldehyde	< 2.0	ppm	ASTM F2013
Color b	> 75.0		ASTM D6290
Color L	< 6.00		ASTM D6290
Crystallinity	> 45	%	
Moisture	< 0.30	%	
Weight - of 20 Chips	330.0	mg	
Blow Molding Drying Temperature	165 to 175	°C	
Blow Molding Drying Time	5.0 to 6.0	hr	
Blow Molding Temperature	270 to 290	°C	
Thermal	Nominal Value	Unit	
Melting Temperature	240 to 250	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT