

SABIC® LDPE 2015N0

Low Density Polyethylene

Saudi Basic Industries Corporation (SABIC)

Message:

SABIC® LDPE 2015N0 is an additive free standard CTR® tubular grade for masterbatch with a high purity and a medium viscosity.

Application

SABIC® LDPE 2015T is typically suitable for masterbatches in film applications with a very high loading of carbon black, titanium dioxide or pigment loading.

This product is not intended for and must not be used in any pharmaceutical/medical applications.

General Information			
Features	Additive Free		
	High Purity		
	Low Density		
	Medium Viscosity		
Uses	Compounding		
	Masterbatch		
Processing Method	Compounding		
Physical	Nominal Value	Unit	Test Method
Density	0.920	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	15	g/10 min	ISO 1133
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	85.0	°C	ISO 306/A
Melting Temperature (DSC)	108	°C	DIN 53765
Enthalpy Change	105	J/g	DIN 53765

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT