POLYPRO® 5150H

Polypropylene Homopolymer

YUHWA Korea Petrochemical Ind. Co., Ltd.

Message:

YUHWA POLYPRO® Meltblown grades are polypropylene homopolymer particularly suitable for non-woven products and pelletized form manufactured by newly developed KPIC process. YUHWA POLYPRO® Meltblown grades having very low viscosity and narow MWD are designed to fulfil the needs in each application.

General Information			
Features	General Purpose Good Processability		
	High Flow		
	Homopolymer Low Viscosity Narrow Molecular Weight Distribution		
Uses	Fibers Industrial Applications Meltblown Nonwovens Nonwovens		
RoHS Compliance	RoHS Compliant		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	1500	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

