# OP - PC - Filled/Lubricated 15 PTFE-30GF

### Polycarbonate

**Oxford Polymers** 

#### Message:

OP - PC - Filled/Lubricated 15 PTFE-30GF is a Polycarbonate (PC) material filled with 30% glass fiber. It is available in North America for injection molding. Important attributes of OP - PC - Filled/Lubricated 15 PTFE-30GF are: Good Mold Release Lubricated Mold Release Agent

General Information					
Filler / Reinforcement	Glass Fiber,30% Filler by Weight				
Additive	Mold Release				
	PTFE Lubricant (15%)				
Features	Good Mold Release				
	Lubricated				
Appearance	Colors Available				
Forms	Pellets				
Processing Method	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.54	g/cm³	ASTM D792		
Molding Shrinkage - Flow (3.18 mm)	0.20	%	ASTM D955		
Water Absorption (Saturation)	0.14	%	ASTM D570		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength	117	MPa	ASTM D638		
Tensile Elongation (Break)	3.0	%	ASTM D638		
Flexural Modulus	8270	MPa	ASTM D790		
Flexural Strength	148	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C, 3.18 mm)	110	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load (1.8					
MPa, Unannealed)	143	°C	ASTM D648		
Injection	Nominal Value	Unit			
Drying Temperature	121	°C			
Drying Time	3.0 to 4.0	hr			
Rear Temperature	288 to 299	°C			
Middle Temperature	288 to 299	°C			
Front Temperature	299 to 316	°C			
Nozzle Temperature	299 to 316	°C			

Processing (Melt) Temp	299 to 327	°C	
Mold Temperature	82.2 to 116	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

