

Guang Sung PVC GPMA80T

Polyvinyl Chloride
Guang Sung Plastics (GSPL)

Message:
Guang Sung PVC GPMA80T is a Polyvinyl Chloride product. It can be processed by extrusion and is available in Asia Pacific. Applications of Guang Sung PVC GPMA80T include automotive and coating applications. Primary characteristic: rohs compliant.

General Information			
Uses	Automotive Interior Parts		
	Automotive Interior Trim		
	Protective Coverings		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Extrusion		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A, 5 sec)	82		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	9.01	MPa	ASTM D412
Tensile Strength (Yield)	14.9	MPa	ASTM D412
Tensile Elongation (Break)	340	%	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT