

OxyVinyls® 155F

Polyvinyl Chloride Homopolymer

OxyVinyls, LP

Message:

OxyVinyls® 155F is a Polyvinyl Chloride Homopolymer (PVC Homopolymer) product. It can be processed by foam processing or injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of OxyVinyls® 155F include additive/masterbatch and foam.

Characteristics include:

High Flow

Homopolymer

General Information	
Features	Foamable
	High Flow
	Homopolymer
Uses	Color Concentrates
	Foam
	Masterbatch
Agency Ratings	EU 10/2011
Appearance	White
Forms	Powder
Processing Method	Foam Processing
	Injection Molding

Physical	Nominal Value	Unit	Test Method
Apparent Density	0.54 to 0.59	g/cm ³	Internal Method
K-Value	49.0 to 50.0		
Contamination	< 10	number/kg	Internal Method
Inherent Viscosity	0.50 to 0.54	dl/g	Internal Method
Particle Size			Malvern
% Retained on Pan	< 20.0	%	
% Retained on 200 mesh	< 50.0	%	
% Retained on 40 mesh	< 0.500	%	
% Retained on 60 mesh	< 2.00	%	
Relative Viscosity	1.58 to 1.62		
CAS Number	9002-86-2		
Flow Time	< 18.0	sec	Internal Method
Porosity	0.170 to 0.270	cm ³ /g	Internal Method
Residual Monomer	< 1	ppm	Internal Method
Volatiles	< 0.15	%	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

