

NEOFLON™ LP-1030

Fluoropolymer

Daikin Fluorochemicals (China) Co., Ltd.

Message:

NEOFLON CPT is a new type of fluoropolymer having excellent barrier properties to all kinds of organic solvents and high active acids especially for HF, HCl, HNO₃.

It is designed to adhere to other plastics. It is suitable for extrusion in multi-layer tubes, films, etc.

Features

Suitable for tubes and sheets for semiconductors and chemical applications. Multi-layer tubes with PFA have already been proven as low permeable tubes in many customers.

General Information		
Features	Barrier Resin	
	Good Adhesion	
Uses	Multilayer Film	
	Sheet	
	Tubing	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Melt Mass-Flow Rate (MFR)	5.0 to 10	g/10 min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

