

# Hifax TRC 779P HA 9B9 BLACK

Polyolefin

LyondellBasell Industries

## Message:

Hifax TRC 779P HA 9B9 BLACK is a talc filled impact modified grade that is typically used for exterior trim applications that has excellent Impact-Stiffness balance and good flowability properties.

General Information			
Filler / Reinforcement	Talc filler		
Additive	Impact modifier		
Features	Good dimensional stability		
	Impact modification		
	Rigid, good		
	Impact resistance, good		
	Sprayable		
	Good formability		
	Good liquidity		
Uses	Car exterior decoration		
	Outdoor application		
Appearance	Black		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density (23°C)	1.04	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	25	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield, 23°C)	18.0	MPa	ISO 527-2
Flexural Modulus (23°C)	1700	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	30	kJ/m <sup>2</sup>	ISO 179

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

