

Ablefilm ECF564AHF

Epoxy; Epoxide
Henkel Ablestik

Message:

Ablefilm ECF564AHF is an Epoxy; Epoxide (Epoxy) material filled with silver. It is available in North America.
Important attributes of Ablefilm ECF564AHF are:
Conductive
High Purity
Typical applications include:
Adhesives/Tapes
Film

General Information		
Filler / Reinforcement	Silver	
Features	Electrically Conductive	
	Good Electrical Properties	
	High Purity	
	Low to No Outgassing	
Uses	Adhesives	
	Film	
Forms	Pellets	
Thermoset	Nominal Value	Unit
Pot Life (23°C)	4300	min
Shelf Life (-40°C)	52	wk
Demold Time (150°C)	120	min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT