

Kumsollan® KSE6160

Styrene Ethylene Butylene Styrene Block Copolymer

Shanghai KumhoSunny Plastics Co., Ltd.

Message:

KUMSOLLAN® KSU 61 series products are the blends of SEBS and thermoplastic polyurethane, and second injection molding can be used with PC, ABS, PBT, PMMA plastic, with good adhesion. KUMSOLLAN® is widely used in automobile, household, electrical and electronic, wire and cable, and daily necessities etc.

General Information			
Features	Good Adhesion		
Uses	Automotive Applications		
	Consumer Applications		
	Electrical/Electronic Applications		
	Household Goods		
	Wire & Cable Applications		
UL File Number	E254819		
	E65424		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.09	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.90 to 1.3	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	62		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	6.00	MPa	ASTM D412
Tensile Elongation (Break)	> 600	%	ASTM D412

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT