

PPO™ 843 resin

Polyphenylene Ether + PS

SABIC Innovative Plastics

Message:

PPO* 843 resin is a medium-high molecular weight copolymer based on Polyphenylene Ether (PPE) and Siloxane. PPO* is intended for use as an additive or a building block in a variety of thermoplastics and thermoplastic elastomers like Styrenic Block Copolymers. PPO* resin can be used to improve properties like Heat Distortion and Creep Resistance. It is hydrolytically stable and non-hydroscopic (typically less than 0.2% water uptake). The polymer is soluble in common organic solvents like toluene, chloroform, and THF. Chemical name: PPE-Siloxane copolymer Formula: $(C_8H_8O)_n(SiC_2H_6O)_m$
Regulatory Status: Complies with EC Reg. No. 10/2011 as amended through EC Reg. No. 2015/174.

General Information			
Features	Copolymer Hydrolysis stability Medium wide molecular weight distribution		
Uses	Additive		
Agency Ratings	Europe 10/1/2011 12:00:00 AM		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Density ¹	0.476	g/cm ³	ISO 1183
D	2.60		Internal method
Mean Particle Size	400.0	µm	Internal method
Mn	14800		Internal method
Mw	36000		Internal method
Phenolic End-group Content	1000	ppm	Internal method
Tg (half width)	216	°C	Internal method
Intrinsic Viscosity	0.40	dl/g	Internal method
Toluene Content		ppm	Internal method
NOTE			

1. Bulk Density

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT