

APEX® 78-A272-A

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX® 78-A272-A is a flexible polyvinyl chloride material. This product is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. The processing method is: extrusion.

APEX® The main features of 78-A272-A are:

- ROHS certification
- Flame Retardant

Typical application areas include:

- Wire and cable
- Electrical/electronic applications

General Information			
Features	Flame retardancy		
Uses	Cable sheath		
Wire Types	CL2		
	CL3		
	CMP		
Agency Ratings	NEC Article 725		
	NEC Article 800		
RoHS Compliance	RoHS compliance		
Appearance	Clear/transparent		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	84		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	17.7	MPa	ASTM D638
Tensile Elongation (Break)	340	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	90.0	°C	ASTM D794
Brittleness Temperature	-32.0	°C	ASTM D746
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	27	%	ASTM D2863
Additional Information			
温度额定值:90 °C耐日光性UL认证:否最大伸长保持率,UL 1581,烘箱老化,7天,121°C:80 %拉伸强度保持率,UL 1581,烘箱老化,7天,121°C: 107 %			
Extrusion	Nominal Value	Unit	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT