

Technother® A-SV15-T

Polybutylene Terephthalate

Poly Plastic

Message:

Technother® A-SV15-T is a Polybutylene Terephthalate (PBT) product filled with glass fiber. It is available in Europe.

General Information		
Filler / Reinforcement	Glass Fiber	
Physical	Nominal Value	Unit
Density	1.41	g/cm ³
Molding Shrinkage	0.50 to 1.1	%
Water Absorption (Equilibrium, 23°C, 50% RH)	0.20	%
Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	100	MPa
Tensile Strain (Break)	2.7	%
Impact	Nominal Value	Unit
Charpy Unnotched Impact Strength (20°C)	47	kJ/m ²
Thermal	Nominal Value	Unit
Heat Deflection Temperature (1.8 MPa, Unannealed)	205	°C
Melting Temperature	225	°C
Electrical	Nominal Value	Unit
Surface Resistivity	1.0E+14	ohms
Volume Resistivity	1.0E+14	ohms·cm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT