Evermore PUR SS-302P

Polyurethane

Evermore Chemical Industry Co., Ltd.

Message:

Evermore PUR SS-302P is a Polyurethane product. It is available in Asia Pacific. Typical application: Printing Applications. Primary characteristic: antiblock.

General Information			
Additive	Antiblock		
Features	Antiblocking		
	Dispersible		
	Good Color Stability		
Uses	Printing Ink		
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	2.94 to 4.90	MPa	ASTM D412
Tensile Strength (Yield)	19.6 to 39.2	MPa	ASTM D412
Tensile Elongation (Break)	300 to 600	%	ASTM D412
Fill Analysis	Nominal Value	Unit	Test Method
Melt Viscosity (25.0°C)	20.0 to 35.0	Pa·s	ASTM D3835
Additional Information	Nominal Value	Unit	Test Method
Non-Volatile Content	34 to 36	%	
Solvents	MEK, DMF, ANONE, MIBK		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

