

Geon™ Vinyl Flexible 90401

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™Vinyl Flexible 90401 is a flexible polyvinyl chloride product. It can be processed by blow molding and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Typical application areas are: automotive industry. The main characteristics are: low gloss.

General Information			
Features	Gloss, low		
Uses	Application in Automobile Field		
	Car interior equipment		
Forms	Particle		
Processing Method	Blow molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.24	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	75		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹ (Break)	14.2	MPa	ASTM D638
Tensile Elongation ² (Break)	310	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength ³	36.0	kN/m	ASTM D624
Thermal	Nominal Value		Test Method
Cold Flexibility ⁴ (-29°C, 1.91 mm)	Pass		GM 9503P
Automotive Burn Test	0	mm/min	FMVSS 302
Fogging ⁵	86	%	SAE J1756
Xenon Weatherometer ⁶	Pass		SAE J1960
Optical	Nominal Value		Test Method
Gardner Gloss (60°)	4		ASTM D523
Additional Information	Nominal Value		Test Method

注释:汽车OEM认证.

NOTE	
1.	Type 4, 510mm/min
2.	Type 4, 510mm/min
3.	C mold, 510mm/min
4.	25 mm,4 hours
5.	3 hours, 212 °F(100°C),70 °F(21°C), after 1 hour
6.	Internal, 1240 kJ/m, all colors, dE *<3.0

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

