Xuchuan XCY-5580

Polyurethane

Xuchuan Chemical (Suzhou) Co., Ltd

Message:

Xuchuan XCY-5580 is a Polyurethane product. It is available in Asia Pacific. Applications of Xuchuan XCY-5580 include bags/liners and consumer goods. Primary characteristic: high hardness.

| General Information | | | |
|------------------------------|---------------|------|--|
| Features | High Hardness | | |
| Uses | Bags | | |
| | Footwear | | |
| | | | |
| Physical | Nominal Value | Unit | |
| Solids Content | 24 to 26 | % | |
| Viscosity (25°C) | 50.0 to 80.0 | Pa·s | |
| Solvents | DMF, TOL, IPA | | |
| Elastomers | Nominal Value | Unit | |
| Tensile Stress (100% Strain) | 7.85 | MPa | |
| Tensile Strength (Break) | 49.0 | MPa | |
| Tensile Elongation (Break) | 350 | % | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

