# Huaxia Shenzhou FKM DS2602

#### Fluoroelastomer

Shandong Huaxia Shenzhou New Material Co., Ltd.

#### Message:

Fluorous rubber (FKM-DS2600), commonly called 2# rubber, is white elastomer and copolymer of VDF and hexafluoropropylene, with fluorine content of over 66%. The product processed and vulcanized by raw fluorous rubber (DS2600), featured by good mechanical property and excellent oil resistance (fuels, synthetic oils, lubricating oils) and heat resistance, is an indispensable material for modern aviation, rocket, missile, space flight, and other top technologies and industries.

Characteristic: Medium Mooney viscosity

Application: Compression molding and injection molding O-rings, extrusion hoses, etc.

General Information			
Features	Copolymer		
	Fuel Resistant		
	Good Corrosion Resistance		
	Good Weather Resistance		
	High Heat Resistance		
	Medium Viscosity		
	Oil Resistant		
	Ozone Resistant		
	Radiation (Gamma) Resistant		
Uses	Aerospace Applications		
	Cable Jacketing		
	Coating Applications		
	Diaphragms		
	Gaskets		
	Hose		
	Piping		
	Seals		
Appearance	Transparent - Slight Yellow		
	White		
Forms	Film		
Processing Method	Compression Molding		
	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	
Specific Gravity	1.80 to 1.84	g/cm³	
Mooney Viscosity (ML 1+10, 121°C)	40 to 60	MU	

Elastomers	Nominal Value	Unit
Tensile Strength		
	> 11.0	MPa
1	> 9.00	MPa
Tensile Elongation		
Break	> 150	%
Break <sup>2</sup>	> 120	%
Compression Set <sup>3</sup> (200°C, 24 hr)	< 25	%
NOTE		
1.	Aged for 24 hr at 275°C	
2.	Aged for 24 hr at 275°C	
3.	Bisphenol AF, compression ratio 30%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

