

# Paracril® CJLT

Acrylonitrile Butadiene Rubber

INSA

## Message:

Description:

Superior oil resistance.

Good processing properties.

Low water absorption.

Cold polymerized.

Non staining stabilizer.

Applications:

Seals, o-rings, packings and grommets.

Printing blankets and rolls.

Oil field specialties.

Fuel hose.

Mechanical goods.

## General Information

Features	Good Processability
	Low to No Water Absorption
	Oil Resistant
	Stain Resistant

Uses	Grommets
	Hose
	Oil/Gas Applications
	Rollers
	Seals

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.01	g/cm <sup>3</sup>	ASTM D297
Mooney Viscosity (ML 1+4, 100°C)	43 to 57	MU	ASTM D1646
ACN Content - Bound	38.2 to 41.2	wt%	Internal Method
Ash Content	< 0.8	wt%	ASTM D5667
Volatile Matter	< 1.0	wt%	ASTM D5668

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: [sales@su-jiao.com](mailto:sales@su-jiao.com)

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

