

# SUMILITE® PVC VSS-F110

Polyvinyl Chloride  
Sumitomo Bakelite Co., Ltd.

Message:

SUMILITE®PVC VSS-F110 is a polyvinyl chloride product. It is available in North America. SUMILITE®The application fields of PVC VSS-F110 include thin plates and medical/health care.

General Information			
Uses	Sheet		
	Drug		
Forms	Particle		
Films	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D882
MD: Yield	60.8	MPa	ASTM D882
TD: Yield	58.8	MPa	ASTM D882
Tensile Elongation			ASTM D882
MD: Fracture	120	%	ASTM D882
TD: Fracture	100	%	ASTM D882
Water Vapor Transmission	3.3	g/m <sup>2</sup> /24 hr	ASTM E96
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	80.0	°C	ASTM D1525
Optical	Nominal Value	Unit	Test Method
Transmittance (250 μm)	89.0	%	ASTM D1003
Haze (250 μm)	3.0	%	ASTM D1003
Additional Information			

The values listed as ASTM D882 were tested in accordance with JIS K6734The value listed as ASTM D1525 was tested in accordance with JIS K7206The values listed as ASTM D1003 were tested in accordance with JIS K7105The value listed as ASTM E96 was tested in accordance with JIS Z0208Notched Izod Impact Strength, JIS K7110: 3.0 KJ/m<sup>2</sup>

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT