

Adstif EA5076

Polypropylene Copolymer
PolyMirae

Message:

"Adstif" EA5076 is a medium flow heterophasic copolymer development grade with outstanding mechanical properties. The product features an easy processability and an excellent stiffness combined with good impact properties and good gloss.

General Information			
Features	Good Impact Resistance		
	Good Processability		
	Good Stiffness		
	High Flow		
	High Gloss		
	Impact Copolymer		
Uses	Automotive Applications		
	Compounding		
	Electrical/Electronic Applications		
RoHS Compliance	Contact Manufacturer		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	110	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	105		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	31.4	MPa	ASTM D638
Tensile Elongation (Yield)	4.0	%	ASTM D638
Flexural Modulus	1570	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-20°C	20	J/m	
23°C	39	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	128	°C	ASTM D648
Vicat Softening Temperature	152	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT