THERMOLAST® K TF6BTL (Series: FC/AP)

Thermoplastic Elastomer

KRAIBURG TPE

Message:

The FC/AP Series is your natural-colored and translucent material solution for applications with food contact. The series' features include an excellent adhesion to PP.

Typical applications

Function and design elements

Grip applications

Household articles

Packaging (for food and careproducts)

Razors

Seals

Toothbrushes

Toys

Material advantages

Adhesion to PP

Applications with food contact

Easy coloring (compounds in natural colors)

EN71/3

Excellent mechanical properties

Excellent processing behavior

FDA compliant

Halogen-free

In natural or translucent available

Pleasant surface feel (Soft touch)

Recyclable

Regulation (EU) 10/2011

General Information	
Features	Food Contact Acceptable
	Good Adhesion
	Good Processability
	Halogen Free
	Recyclable Material
	Soft
Uses	Food Packaging
	Household Goods
	Non-specific Food Applications
	Packaging
	Seals
	Toothbrush Handles
	Toys
Agency Ratings	EN 71-3
	EU 10/2011

FDA Unspecified Rating

Appearance	Translucent			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Density	0.880	g/cm³	ISO 1183	
Hardness	Nominal Value	Unit	Test Method	
Shore Hardness (Shore A)	60		ISO 7619	
Elastomers	Nominal Value	Unit	Test Method	
Tensile Stress ¹ (Yield)	9.00	МРа	ISO 37	
Tensile Elongation ² (Break)	770	%	ISO 37	
Tear Strength ³	14	kN/m	ISO 34-1	
Injection	Nominal Value	Unit		
Drying Temperature	60.0 to 80.0	°C		
Drying Time	2.0 to 4.0	hr		
Rear Temperature	180	°C		
Middle Temperature	200	°C		
Front Temperature	220	°C		
Mold Temperature	25.0 to 40.0	°C		
Injection Pressure	20.0 to 100	MPa		
Back Pressure	2.00 to 10.0	MPa		
NOTE				
1.	Type S2, 200 mm/min	Type S2, 200 mm/min		
2.	Type S2, 200 mm/min	Type S2, 200 mm/min		
3.	Method Bb, Angle (Nicked)	Method Bb, Angle (Nicked)		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

