

APEX® 60002

Flexible Polyvinyl Chloride

Teknor Apex Company

Message:

APEX®60002 is a flexible polyvinyl chloride material. This product is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. The processing method is: extrusion.

APEX®The main features of the 60002 are:

ROHS certification

Flame Retardant

Typical application areas include:

Wire and cable

Electrical/electronic applications

General Information			
Features	Flame retardancy		
Uses	Communication wire insulation material		
Wire Types	CL2R		
	CL3R		
	CMR		
	FPLP		
	MPR		
	OFNR		
Agency Ratings	NEC Article 725		
	NEC Article 760		
	NEC Article 770		
	NEC Article 800		
	UL 13		
	UL 1424		
RoHS Compliance	UL 444		
	RoHS compliance		
	Opacity		
Appearance	Particle		
Forms	Extrusion		
Processing Method			
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.30	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C, 10 sec)	90		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	24.1	MPa	ASTM D638
Tensile Elongation (Break)	270	%	ASTM D638

Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-10.0	°C	ASTM D746
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	30	%	ASTM D2863
Additional Information			

温度额定值:90 °C

Extrusion	Nominal Value	Unit
Melt Temperature	199	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

