

Comai 408-2 NT

Polypropylene Copolymer

Comai Ltda

Message:

Comai 408-2 NT is a Polypropylene Copolymer (PP Copolymer) product filled with 20% glass fiber. It is available in Latin America. Typical application: Industrial Applications.

Characteristics include:

Copolymer

Rigid

General Information			
Filler / Reinforcement	Glass Fiber,20% Filler by Weight		
Features	Copolymer		
	High Rigidity		
Uses	Industrial Applications		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.05	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	8.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	37.9	MPa	ASTM D638
Flexural Modulus	2760	MPa	ASTM D790
Flexural Strength	51.7	MPa	ASTM D790

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT