ESTACARB PC 0860GF V1

Polycarbonate

Cossa Polimeri S.r.l.

Message:

ESTACARB PC 0860GF V1 is a polycarbonate (PC) product, which contains a 30% glass fiber reinforced material. It is available in Europe. Typical application areas are: electrical/electronic applications.

Features include:

flame retardant/rated flame

Flame Retardant

Heat resistance

General Information			
Filler / Reinforcement	Glass fiber reinforced material, 30% filler by weight		
Features	Heat resistance, medium		
	Flame retardancy		
Uses	Electrical/Electronic Applications		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.42	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (300°C/1.2 kg)	8.0	g/10 min	ASTM D1238
Molding Shrinkage - Flow	0.20 - 0.40	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	70.0	МРа	ASTM D638
Tensile Elongation (Yield)	4.0	%	ASTM D638
Flexural Modulus	5400	МРа	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
0°C	70	J/m	ASTM D256
23°C	80	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature			
	150	°C	ASTM D1525 ¹
	147	°C	ASTM D1525 ²
Ball Indentation Temperature	135	°C	IEC 60598-1
Flammability	Nominal Value	Unit	Test Method
Flame Rating			UL 94
1.60 mm	V-1		UL 94
3.20 mm	V-1		UL 94
Glow Wire Ignition Temperature	960	°C	IEC 60695-2-13
Additional Information			

NOTE		
1.	压 力1 (10N)	
2		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

