SILPURAN® 8020/60

Silicone

Wacker Chemie AG

Message:

Cured Properties

Silicone Rubber, HTV
Gaskets, Plastics and Rubber Processing
Membranes, Pharmaceuticals & Healthcare
Balloons, Pharmaceuticals & Healthcare
Seals (HealthCare / Pharma), Pharmaceuticals & Healthcare
Valves (HealthCare / Pharma), Pharmaceuticals & Healthcare

General Information										
Features	Biocompatible									
	BPA Free Breathable Good Chemical Resistance Good Flexibility Good Sterilizability Good Thermal Stability									
						High Gas Permeability High Heat Resistance				
										High Purity Low to No Odor
							Low to No Water Absorption			
							Non-Toxic			
							Steam Resistant			
	Uses	Body Implants								
		Medical Devices								
		Medical/Healthcare Applications								
Pharmaceuticals										
Agency Ratings	ISO 10993									
	USP Class VI									
Processing Method	Compression Molding									
	Press Molding									
Uncured Properties	Nominal Value	Unit	Test Method							
Color	Clear/Transparent									
Density	1.16	g/cm³	DIN 53479							

Nominal Value

Unit

Test Method

Shore Hardness (Shore A)	60		DIN 53505
Tensile Strength	11.2	MPa	DIN 53504
Tensile Elongation at Break	670	%	DIN 53504
Compression Set	30	%	DIN ISO 815-B
Tear Strength	31.0	kN/m	ASTM D624B
Rebound Resilience	57	%	DIN 53512

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

