

# Europrene Latice® 1142

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

## Message:

Europrene Latice 1142 is an aqueous dispersion of a carboxylated styrene-butadiene copolymer obtained using synthetic anionic emulsifiers.

### Key Features

Europrene Latice 1142 is specifically designed to obtain and extremely good runnability.

### Main Applications

Europrene Latice 1142 is used for offset paper (when high gloss is required).

General Information			
Features	Copolymer		
Uses	Coating application		
	Paper coating		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
pH	6.0		ASTM D1417
Surface Tension	49	mN/m	ASTM D1417
Solids Content	50.0	wt%	ASTM D1417
Brokfield Viscosity <sup>1</sup> (25°C)	350	mPa · s	ASTM D1417
NOTE			
1.	20 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

