Moplen HP400M

Polypropylene

LyondellBasell Industries

Message:

Moplen HP400M is a homopolymer for injection moulding. The main applications of Moplen HP400M are closures, containers and housewares.

General Information				
Features	Food Contact Acceptable Good Flow			
	Good Impact Resistance			
	Good Stiffness			
Uses	Caps			
	Closures			
	Containers	Containers		
	Household Goods			
	Sporting Goods			
	Toys			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	0.900	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (230°C/2.10				
kg)	7.5	g/10 min	ASTM D1238	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	34.0	MPa	ASTM D638	
Tensile Elongation (Yield)	10	%	ASTM D638	
Flexural Modulus	1450	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact	27	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (0. MPa, Unannealed)	45 96.0	°C	ASTM D648	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

