

# Moplen HP561X

Polypropylene

PolyMirae

## Message:

Moplen HP561X is New generation Melt-Blown grade of Pellet type made by "New process and catalyst technology".

Moplen HP561X shows better processing, color and thermal stability than general Melt-Blown grade of flake type.

Moplen HP561X has narrow MWD, this product is typically used in Diaper and Air filter applications high barrier properties are required.

General Information			
Features	Barrier Resin		
	Good Color Stability		
	Good Processability		
	Good Thermal Stability		
	Narrow Molecular Weight Distribution		
Uses	Filtration Media		
	Masterbatch		
	Spunbond Nonwovens		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	800	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

