

Unichem 9732NC-BLACK-55

Rigid Polyvinyl Chloride

Colorite Polymers

Message:

Unichem 9732NC-BLACK-55 is a semi-rigid vinyl compound designed for automotive profile extrusion. This compound utilizes a well balanced lubrication-stabilizer system which assures trouble free extrusion.

General Information			
Features	Semi Rigid		
Uses	Application in Automobile Field Automotive exterior parts Car exterior decoration Profile		
Appearance	Black		
Forms	Particle		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.32	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	55		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 100% Secant	20.3	MPa	ASTM D638
Tensile Strength (Yield)	21.7	MPa	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Additional Information			
Volatility, 24 hrs, 185°F: 0.53% loss			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT