

# Jam HDPE HC7260

High Density Polyethylene  
Jam Petrochemical Company

Message:

Jam HDPE HC7260 is a High Density Polyethylene product. It can be processed by injection molding and is available in Africa & Middle East. Primary characteristic: homopolymer.

General Information			
Features	Homopolymer		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.958 to 0.964	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR)			ISO 1133
190°C/2.16 kg	6.0 to 10	g/10 min	
190°C/5.0 kg	20 to 26	g/10 min	
Flow Rate Ratio <sup>1</sup>	2.50 to 3.40		
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C, Compression Molded)	> 4.0	kJ/m <sup>2</sup>	ISO 179/1eA
NOTE			

1. 5/2.16, FRR values are statistical and calculated by dividing MFR values.

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

  
WECHAT