

EZ-Spray® Foam

Silicone
Smooth-On, Inc

Message:

EZ~Spray Foam is a polyurethane foam compound that can be conveniently sprayed using Smooth-On's EZ~Spray Junior System. Foam cures quickly to strong, lightweight and impact resistant 12 lb. rigid foam that can be used for a variety of applications including making lightweight castings. Foam can also be sprayed over certain rubber mold configurations as a mother mold material. For more information, refer to Smooth-On's EZ~Spray Junior manual and video.

General Information			
Features	Foamable		
	Good Impact Resistance		
	Good Strength		
Uses	Foam		
	Molds/Dies/Tools		
Appearance	Tan		
Processing Method	Casting		
Physical	Nominal Value	Unit	Test Method
Specific Gravity			
--	0.190	g/cm ³	ASTM D792
--	0.192	g/cm ³	
Specific Volume	5.20	cm ³ /g	
Viscosity - Mixed Part A + B	Variable		
Mixing Ratio	1A:1B by volume		
Thermoset	Nominal Value	Unit	Test Method
Pot Life	0.22	min	
Thermoset Mix Viscosity			ASTM D2393
-- ¹	1000	cP	
-- ²	200	cP	
Demold Time	2.0	min	
NOTE			
1.	Part B		
2.	Part A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

