

Teflon® FFR 550

Fluoropolymer
DuPont Fluoropolymers

Message:

DuPont™ Teflon® FFR 550 is fluoropolymer compounded with a nucleating package. The nucleating package in this resin, when combined with nitrogen gas injection, forms uniform foam cells in the insulation.

General Information	
Additive	Nucleating Agent
Features	Foamable
	Nucleated
Uses	Coaxial Cable Insulation
	Foam
Appearance	White
Forms	Pellets
Processing Method	Extrusion
	Foam Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.13	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR)	14	g/10 min	ASTM D2116
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature	260	°C	ASTM D3418
Electrical	Nominal Value		Test Method
Dielectric Constant			ASTM D2520
100 kHz	2.05		
1 MHz	2.03		
600 MHz	2.00		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT