## Daelim Po1y® PP-333K

Polypropylene Random Copolymer

DAELIM INDUSTRIAL CO., LTD.

## Message:

Daelim Po1y®PP-333K is a polypropylene random copolymer (PP random copolymer) product. It can be processed by injection molding and is available in the Asia-Pacific region. Daelim Po1y®PP-333K application areas include home applications and containers. Features include: high gloss Copolymer Good processability accessible food Rapid Prototyping Cycle

General Information				
Features	Highlight			
	Workability, good			
	Fast molding cycle			
	Definition, high			
	Compliance of Food Exposure			
	Random copolymer			
	Excellent appearance			
Uses	Household goods			
	Food container			
Forms	Particle			
Processing Method	Injection molding			
Physical	Nominal Value	Unit	Test Method	
Density	0.900	g/cm³	ASTM D1505	
Melt Mass-Flow Rate (MFR) (230°C/2.16				
kg)	24	g/10 min	ASTM D1238	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	110		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	27.5	MPa	ASTM D638	
Tensile Elongation (Yield)	20	%	ASTM D638	
Flexural Modulus	1230	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact			ASTM D256	
-20°C	29	J/m	ASTM D256	
23°C	49	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	

Deflection Temperature Under Load (0.45				
MPa, Unannealed)	130	°C	ASTM D648	
Vicat Softening Temperature	85.0	°C	ASTM D1525	
Optical	Nominal Value	Unit	Test Method	
Optical Haze	Nominal Value	Unit %	Test Method ASTM D1003	

Accelerated Oven Aging in Air, ASTM D3012, Forced Circulation at 150°C: 360 hours

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

