

# Moplen HP3097

Polypropylene Homopolymer

LyondellBasell Industries

## Message:

Moplen HP3097 is suitable for extrusion applications. It has a high melt flow rate, a very narrow molecular weight distribution and is in pelletized form. Moplen HP3097 is suitable for the production of meltblown nonwovens and is also used for compounding applications. For regulatory information please refer to Moplen HP3097 Product Stewardship Bulletin (PSB).

General Information	
Features	Homopolymer
	High liquidity
	Narrow molecular weight distribution
Uses	Meltblown Nonwovens
	Composite
	Non-woven fabric
Forms	Particle
Processing Method	Meltblown Nonwovens
	Composite
	Extrusion

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	450	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

