

Geon™ Vinyl Packaging M2715

Rigid Polyvinyl Chloride

PolyOne Corporation

Message:

This product has a translucent low gloss frosted appearance.

General Information			
Features	Food Contact Acceptable		
	High Flow		
	Medium Impact Resistance		
Agency Ratings	FDA Food Contact, Unspecified Rating		
Forms	Pellets		
Processing Method	Injection Blow Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity			
--	1.33	g/cm ³	ASTM D792
--	0.835	g/cm ³	ASTM D1505
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	80		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus ¹	2540	MPa	ASTM D638
Tensile Strength ² (Yield)	48.9	MPa	ASTM D638
Flexural Modulus	2830	MPa	ASTM D790
Flexural Strength	86.2	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm, Injection Molded)	120	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed, 3.18 mm)	19.4	°C	ASTM D648
NOTE			
1.	Type I, 5.1 mm/min		
2.	Type I, 5.1 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

