

# Geon™ Vinyl Fittings M1030

Rigid Polyvinyl Chloride

PolyOne Corporation

## Message:

Geon™ Vinyl Fittings M1030 is a Rigid Polyvinyl Chloride product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Geon™ Vinyl Fittings M1030 include plumbing/piping/potable water and engineering/industrial parts.

General Information			
Features	Medium Flow		
Uses	Fittings		
Agency Ratings	NSF 14		
	NSF 61		
	NSF Type I 3		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.41	g/cm <sup>3</sup>	ASTM D792
Spiral Flow	71.1	cm	
Molding Shrinkage - Flow	0.20 to 0.50	%	ASTM D955
PVC Cell Classification	12454		ASTM D1784
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	74		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus <sup>1</sup>	3030	MPa	ASTM D638
Tensile Strength <sup>2</sup> (Yield)	52.4	MPa	ASTM D638
Flexural Modulus	3030	MPa	ASTM D790
Flexural Strength	87.6	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, 3.18 mm, Injection Molded)	44	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Annealed, 3.18 mm)	70.0	°C	ASTM D648
Injection	Nominal Value	Unit	
Processing (Melt) Temp	199 to 210	°C	
NOTE			
1.	Type I, 5.1 mm/min		
2.	Type I, 5.1 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

