

# BRALEN® SA 200-22

Low Density Polyethylene

Slovnaft Petrochemicals, s.r.o.

## Message:

BRALEN SA 200-22 is a special grade of low density polyethylene. This grade is additives free.

### Applications

BRALEN SA 200-22 is designed for nonwoven textile production. It is well suited also to be used as an ingredient into waxes and electroinsulating materials. In powder form (after grinding) it is used in textile industry.

BRALEN SA 200-22 is suitable for food contact. The product complies with Food Contact Regulations.

General Information			
Features	Additive Free		
	Food Contact Acceptable		
	Low Density		
	Recyclable Material		
Uses	Electronic Insulation		
	Nonwovens		
	Textile Applications		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.915	g/cm <sup>3</sup>	ISO 1183/C
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	200	g/10 min	ISO 1133
Extrusion	Nominal Value	Unit	
Melt Temperature	190 to 280	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT