KPOL-LDPE LD K-1.20/920

Low Density Polyethylene

KPOL Chem Co.

Message:

Low Density Polyethylene Excellent Processability

Characteristics

KPOL Chem LD K- 1.20/922 is a low density polyethylene (LDPE) resin used in a wide range of processing methods such as injection molding, blow moulding and film extrusion. It exhibits very good softness and toughness and good dimensional stability. Is delivered in pellet form and is not additivated .

Applications

Typical customer applications include products with good mechanical properties and high flexibility : Blow Moulding Applications, Bottles For Consumer Goods, Caps & Closures, Sports, Leisure, Toys and lids and champagne corks.

General Information					
Additive	Antioxidant				
Features	Antioxidant				
	BPA Free				
	Good Dimensional Stability				
	Good Flexibility				
	Good Processability				
	Good Toughness				
	Soft				
Uses	Bottles				
	Caps				
	Closures				
	Lids				
	Sporting Goods				
	Toys				
Agency Ratings	FDA 21 CFR 177.1520				
Processing Method	Blow Molding				
	Extrusion				
	Film Extrusion				
	Injection Molding				
Physical	Nominal Value	Unit	Test Method		
Density	0.920	g/cm³	ASTM D1505		
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.2	g/10 min	ASTM D1238		
Hardness	Nominal Value	Unit	Test Method		
Durometer Hardness (Shore D)	48		ASTM D2240		
Mechanical	Nominal Value	Unit	Test Method		

Tensile Strength			ASTM D638	
Yield	14.0	MPa		
Break	12.0	MPa		
Thermal	Nominal Value	Unit	Test Method	
Vicat Softening Temperature	88.0	°C	ASTM D1525 ¹	
NOTE				
1.	Rate A (50°C/h), Loading 1 (10 N)			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

