Epoxies, Ect. 20-3004 LV

Epoxy; Epoxide

Epoxies, Etc.

Message:

20-3004 LV & HV are two component chemical resistance epoxy systems. They were developed for potting, coating, and adhesive applications requiring superior chemical resistance. They exhibit outstanding bonds to a variety of substrates.

20-3004 LV is a low viscosity self leveling system. 20-3004 HV is a high viscosity non-sag version.

Features:

Excellent chemical resistance

Excellent water resistance

Excellent adhesion to metals & plastics

DOT noncorrosive

General Information

Features	Bondability Good Adhesion Good Chemical Resistance Low to No Water Absorption					
				Low Viscosity		
				Uses	Adhesives	
	Coating Applications					
Appearance	Grey					
Processing Method	Encapsulating					
	Potting					
Thermal	Nominal Value	Unit				
Glass Transition Temperature	50.0	°C				
Additional Information	Nominal Value	Unit				
Operating Temperature	-50.0 to 140	°C				
Uncured Properties	Nominal Value	Unit				
Color						
1	Black					
2	Grey					
3	White					
Mix Ratio by Weight (PBW)						
Part A	2.0					
Part B	1.0					
Mix Ratio by Volume (PBV)						
Part A	100					
Part B	45					

Density			
25°C ⁴	1.17	g/cm³	
25°C ⁵	1.17	g/cm³	
Viscosity			
25°C ⁶	5.0	Pa·s	
25°C ⁷	9.0	Pa·s	
Curing Time (25°C)	1.7E+2	hr	
Pot Life ⁸ (25°C)	90	min	
Cured Properties	Nominal Value	Unit	
Shore Hardness (Shore D)	78		
Tensile Strength	52.4	МРа	
Tensile Elongation at Break	3.2	%	
Relative Permittivity	3.61		
Dissipation Factor	0.021		
NOTE			
1.	Part A		
2.	Mixed		
3.	Part B		
4.	Part B		
5.	Part A		
6.	Part B		
7.	Part A		
8.	100 grams		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

