

Neopor® 2300

Expanded Polystyrene

BASF Corporation

Message:

Application

Neopor® is used to manufacture silver-grey coloured foams that have considerably better thermal insulation capacity than conventional EPS products.

Product description

Expandable polystyrene (EPS) containing uniformly distributed flame retardant. Blowing agent: pentane.

Neopor foam insulation is flame retarding and complies with DIN 4102-B1. Additional information pertaining to the fire behavior can be found in the technical information sheet titled "Fire - protection behavior of foams made of Styropor®".

Neopor® 2300 : For blocks and shapes with wall thicknesses over 8 mm

General Information		
Additive	Blowing Agent 2	
	Flame Retardant	
Features	Flame Retardant	
Uses	Foam	
Agency Ratings	DIN 4102/B1	
	EC 1907/2006 (REACH)	
RoHS Compliance	RoHS Compliant	
Appearance	Grey	
Forms	Spheres	
Physical	Nominal Value	Unit
Apparent Density		
-- ¹	0.02	g/cm ³
--	0.02 to 0.03	g/cm ³
Moisture Content	< 3.5	%
Sieve Analysis		
< 700.0 µm	< 2.0	%
0.700 to 1.60 mm	> 96	%
> 1.60 mm	< 2.0	%
Aging - intermediate	0.4 to 2.0	day
Bead Size	0.800 to 1.40	mm
NOTE		
1.	Obtainable in a single pre-foaming operation	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

