# OxyVinyIs® 310

### Polyvinyl Chloride Homopolymer

OxyVinyls, LP

#### Message:

OxyVinyls® 310 is a Polyvinyl Chloride Homopolymer (PVC Homopolymer) product. It can be processed by calendering or extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Characteristics include: Fatigue Resistant High Strength Homopolymer Impact Resistant Wear Resistant

General Information			
Features	Fatigue Resistant		
	Good Abrasion Resistance		
	Good Impact Resistance		
	High Strength		
	Homopolymer		
	Medium Molecular Weight		
Agency Ratings	EU 10/2011		
Appearance	White		
Forms	Powder		
Processing Method	Calendering		
	Extrusion		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.38 to 0.49	g/cm³	Internal Method
K-Value	82.0 to 83.0		
Contamination	< 15	number/kg	Internal Method
Inherent Viscosity	1.4	dl/g	Internal Method
Particle Size			Malvern
% Retained on Pan	< 2.00	%	
% Retained on 200 mesh	< 12.0	%	
% Retained on 40 mesh	< 0.200	%	
% Retained on 60 mesh	< 4.00	%	
Relative Viscosity	3.01 to 3.17		
CAS Number	9002-86-2		
Porosity	0.320 to 0.400	cm³/g	Internal Method
Residual Monomer	< 2	ppm	Internal Method
Volatiles	< 0.30	%	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

