

# POPTREE 6001B

Polyethylene  
POLYROCKS CHEMICAL CO., LTD

Message:

POPTREE 6001B is a Polyethylene product. It is available in Asia Pacific. Typical application: Consumer Goods.

Characteristics include:

Flame Rated  
Chemical Resistant  
Flame Retardant  
High Flow

General Information			
Features	Flame Retardant		
	Good Chemical Resistance		
	High Flow		
Uses	Consumer Applications		
UL File Number	E253482		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.980	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	15	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	10.0	MPa	ASTM D638
Tensile Elongation (Break)	300	%	ASTM D638
Flexural Modulus	175	MPa	ASTM D790
Flexural Strength	8.00	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	460	J/m	ASTM D256
Flammability	Nominal Value		Test Method
Flame Rating			UL 94
1.50 mm, Green/White	V-2		
3.00 mm, Green/White	V-2		
Injection	Nominal Value	Unit	
Processing (Melt) Temp	160 to 180	°C	
Mold Temperature	30.0 to 60.0	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

