

Unichem 4875

Polyvinyl Chloride

Colorite Polymers

Message:

Unichem 4875 is a polyvinyl chloride product. It can be processed by extrusion or injection molding and is available in North America.

Features include:

Good flexibility

Heat resistance

General Information	
Features	Good liquidity Good flexibility Thermal stability, good General
Uses	General
Forms	Particle
Processing Method	Extrusion Injection molding

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.38	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 10 sec)	48		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	5.52	MPa	ASTM D638
Tensile Elongation (Break)	450	%	ASTM D638
Additional Information			
100% Modulus, ASTM D638: 250 psi			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT