

Itenite® 817

Thermoplastic Vulcanizate

ITEN INDUSTRIES

Message:

Itenite® 817 is a Thermoplastic Vulcanizate (TPV) material. It is available in North America.

Important attributes of Itenite® 817 are:

REACH Compliant

RoHS Compliant

General Information			
Agency Ratings	EC 1907/2006 (REACH)		
RoHS Compliance	RoHS Compliant		
Forms	Fiber		
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ¹			
Across Flow : Yield	58.6	MPa	
Flow : Yield	110	MPa	
Flexural Strength			
-- ²	105	MPa	
-- ³	154	MPa	
Compressive Strength			
-- ⁴	80.7	MPa	
-- ⁵	96.5	MPa	
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact ⁶			
Across Flow	58	J/m	ASTM D256
Flow	63	J/m	
Electrical	Nominal Value	Unit	Test Method
Dielectric Strength	12	kV/mm	ASTM D149
Relative Permittivity			ASTM D150
1 MHz ⁷	8.13		
1 MHz ⁸	5.93		
Dissipation Factor			ASTM D150
1 MHz ⁹	0.11		
1 MHz ¹⁰	0.052		
Arc Resistance ¹¹	128	sec	ASTM D495
Dielectric Breakdown			ASTM D149
-- ¹²	4100	V	
-- ¹³	60000	V	
NOTE			
1.	Condition A		

2.	Across Flow, Condition A
3.	Flow, Condition A
4.	Across Flow, Condition A
5.	Flow, Condition A
6.	E48/50
7.	D24/23
8.	Condition A
9.	D24/23
10.	Condition A
11.	Condition A
12.	D48/50
13.	Condition A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

